

# T30 Belt Drive Turntable

- Fully automatic operation keeps LPs scratch free
- 2 speed Belt drive turntable - 33 1/3 and 45 RPM
- Built-in switchable stereo phono/line level pre-amplifier.



**Specification**

**GENERAL SPECIFICATIONS**

- Power supply : AC 230V~, 50Hz
- Power consumption : 3 Watts
- Operating voltage : DC 12V
- Dimensions : 350 (W) x 348 (D) x 95.4 (H) mm
- Weight : 2.8 Kg

**TURNTABLE SECTION**

- 2-speed full-auto
- Motor : DC Motor
- Driving : Belt drive
- Platter : 296mm dia.
- Speed : 33 1/3 and 45 rpm
- Wow and flutter : Less than 0.25%(WTD) at 3KHz (JIS)
- S/N Ratio : More than 50dB (DIN-B)
- Speed Tolerance : 3000Hz +3% , -2%

**TO NEARM SECTION**

- Type : Dynamic balanced straight shaped arm w/soft damping control
- Effective arm length : 195mm
- Tonearm Lead - in point
  - 17cm To be operated within the distance 85+/-0.75mm from the record center
  - 30cm To be operated within the distance 147.3 +/- 0.75mm from the record center
- Tonearm return point
  - To be operated between the distance of 54mm and 62mm from the record center
- Tracking Force adjustment range : 3.5+/-1.0g

**CARTRIDGE SECTION (AT3600LAX)**

- Type : Moving magnet cartridge
- Stylus : Diamond stylus
- Output Voltage

A. Connect with Equalizer 90-216mV at 1KHz  
5cm/sec (HP-4005)

B. Connect without Equalizer 1.5-3.6mV at 1KHz  
5cm/sec (HP-4005)

- Channel Separation : More than 15dB at 1KHz
- Channel Balance : Within 2.5 dB at 1KHz
- Load Impedence : 47K ohm , 100 PF



\*All specifications and apprerances are subject to change without notice. VOXOA reserves the rights to change the design for products improvement.

**VOXOA Co., LTD**

Suite 1801-5,18/F.,Tower 2, China Hong Kong City,  
33 Canton Road, Tsim Sha Tsui, Kowloon, Hong Kong  
http://www.voxoa-pro.com  
Email: service@voxoa-pro.com  
sales@soundshine.com.cn

